



FICHA TÉCNICA

LÁMINA PVC

ESPECIFICACIONES

- **Espesores:** 2mm, 3mm, 4mm, 5mm, 6mm, 10mm, 18mm, 25mm, 30mm
- **Tamaño:** 1.22m x 2.44mts
- **Colores:** Blanco y Negro



ESPECIFICACIONES TÉCNICAS

PVC Foam Sheet - Softer			
Ref	Value		Unit
Type	Softer Surface		-
Thickness	1.5 ~20		mm
Width	1220, 1560, 2050		mm
Length	2000, 2440, 3050		mm
Color	White, Black		-
CACO ₃ Rate	31		%
Environmental for Temperature	23		☒
Density	0.5		g/cm ³
Tensile Strength	12-20		Mpa
Impact Strength	8-15		KJ/m ³
Drop Hammer Impact Strength	Not Broken		-
Length Tolerance	±2		mm
Width Tolerance	±2		mm
Thickness Tolerance	±0.3		mm
Diagonal Line Tolerance	≤5		mm
Surface Density	≤650		kg/m ³
Shore	≥40		D
Variation Rate of Heating Sizes	Length	±2.0	mm
	Width	±2.0	mm
Water Absorption	≤1.0		-
Bending Strength	≥16		Mpa
Vicat Softening Point	Decorative Sheet	≥75	☒
	Industrial Sheet	≥80	☒
Heating Dimensional Variation Raflo	Vertical	-5.0~+5.0	%
	Horizontal	-3.0~+3.0	%
Corrosion Degrees 60☒±2☒5h	35%(m/m)HCL	-2.0~+2.0	G/m ³
	30%(m/m)H ₂ SO ₃	-1.0~+1.0	G/m ³
	40%(m/m)NaOH	-1.0~+1.0	G/m ³
	40%(m/m)HNO ₃	-1.0~+1.0	G/m ³

Test Standard	
Test Requirements	QB/T2463.1-1999
Test Method	GB/T6343-2009;GB/T2411-2008;GB/T1040.2-2006;GB/T1633-2000;GB/T8811-2008;GB/T1034-2008;GB/T9341-2008